

Monster ShockPad

A Field United, Premium ShockPad

PRODUCT ATTRIBUTES

- **8, 10, 12, 15, or 32mm Field United VCR ShockPad**
Upcycled VCR adds extreme force reduction and energy restitution to a variety of surfaces

Comprised of vulcanized composition rubber, Monster ShockPad is designed to be field united to a surface layer. Monster enhances the safety, ergonomic, and acoustic properties of the entire flooring system. Available in 8, 10, 12, 15, or 32mm.



APPLICATIONS

- Functional Training
- Free Weights
- Olympic Style Lifting

BENEFITS

- Ergonomic
- Reduces force from impacts
- Durable
- Provides substrate protection
- Will not break down over time

NOMINAL DIMENSIONS

Available as a standard in rolls. Talk to your local sales rep to determine availability, pricing, minimums, and lead times.

- 8mm x 48" (1.2m)
- 10mm x 48" (1.2m)
- 12mm x 48" (1.2m)
- 15mm x 48" (1.2m)
- 32mm x 48" (1.2m)

For approved surface products, please see the Approved Stacked Systems chart.



Monster ShockPad

TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results		
		8mm 10mm	12mm 15mm 32mm	
Density	ASTM D297	36.8 pcf	44.6 pcf	
Tensile Strength	ASTM D412, Die C	35 psi	63 psi	
Elongation at Break	ASTM D412, Die C	40%	85%	
Compression @100 psi	ASTM F36	30%	36%	
Recovery @100psi	ASTM F36	90%	92%	
Flexibility	ASTM F137	Pass	Pass	
Force Reduction	Deltec Field Tester	22% 27%	35% 38% 57%	
Energy Restitution	Deltec Field Tester	61% 58%	54% 50% 47%	